


TECHNICAL DATA SHEET



Type no.	600 26
Article no.	010600260101
EAN/GTIN no.	9005753011816
Application	Starter battery
Electrical data	
Rated voltage	12V
Rated capacity	100 Ah (K20)
Cold start current	600 A (EN)
Dimensions and weights	
Box	
Length max.	413mm
Width max.	175mm
Box height max.	195mm
Total height max.	220mm
Battery weight	Ca. 28,0 kg (+/- 5 %)
	
Electrolyte density	Approx. 1,28 kg/l
Electrolyte	Diluted sulphuric acid
Items/pallet	36
Pallet ID	Euro pallet
Items per layer	12
Features	
Base hold-down	B00
Layout	0
Terminal	1
Separator	PE bag separator
Degassing	Battery with single degassing
Flame arrester	Not integrated
Performance identification	W3-C2-V2-E1
Maintenance ¹⁾	
Water consumption	W3
Refill water	Distilled or demineralised (DIN 43530)
Self-discharge	Approx. 5 % per month
Charging current	Approx. 1/10 of the rated capacity
Charging voltage ²⁾	max. 14,4 V

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.
original