


TECHNICAL DATA SHEET



Type no.		560 10	
Article no.		010560100101	
Standards		DIN EN 50342-1, 50342-2	
Application		Starter battery	
Electrical data			
Rated voltage		12V	
Rated capacity		60 Ah (K20)	
Cold start current		675 A (EN)	
Dimensions and weights			
Box	US BCI 75		
Length max.	248mm		
Width max.	178mm		
Box height max.	184mm		
Total height max.	184mm		
Battery weight	Ca. 16,5 kg (+/- 5 %)		
Electrolyte density		Approx. 1,28 kg/l	
Electrolyte		Diluted sulphuric acid	
Items/pallet		72	
Pallet ID		Euro pallet	
Items per layer		16	
Features			
Base hold-down		B07	
Layout		1	
Terminal		5	
Separator		PE bag separator	
Degassing		Battery with central degassing	
Flame arrester		Not integrated	
Performance identification		W4 - C2 - V1 - E1	
Maintenance ¹⁾			
Water consumption		W4	
Refill water		Distilled or demineralised (DIN 43530)	
Self-discharge		Approx. 3 % per month	
Charging current		Approx. 1/10 of the rated capacity	
Charging voltage ²⁾		max. 14,8 V	

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2020-09-30 ; Rights relating to changes and errors retained.
original