


# TECHNICAL DATA SHEET



Type no.		560 60
Article no.		010560600101
EAN/GTIN no.		9005753100640
Application		Starter battery
Electrical data		
Rated voltage		12V
Rated capacity		60 Ah (K20)
Cold start current		480 A (EN)
Dimensions and weights		
Box	H5	
Length max.	241mm	
Width max.	175mm	
Box height max.	190mm	
Total height max.	190mm	
Battery weight	Ca. 15,0 kg (+/- 5 %)	
Electrolyte density		Approx. 1,28 kg/l
Electrolyte		Diluted sulphuric acid
Items/pallet		72
Pallet ID		Euro pallet
Items per layer		18
Features		
Base hold-down		B13
Layout		0
Terminal		1
Separator		PE bag separator
Degassing		Battery with central degassing
Flame arrester		Integrated
Performance identification		W4 - C2 - V1 - E1
Maintenance <sup>1)</sup>		
Water consumption		W4
Refill water		Distilled or demineralised (DIN 43530)
Self-discharge		Approx. 3 % per month
Charging current		Approx. 1/10 of the rated capacity
Charging voltage <sup>2)</sup>		max. 14,8 V

<sup>1)</sup> All the listed values relate to room temperature +25° C

<sup>2)</sup> Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2024-05-12 ; Rights relating to changes and errors retained.  
original