

TECHNICAL DATA SHEET



| | |
|--------------------------------|---|
| Type no. | 570 70 |
| Article no. | 010570700101 |
| EAN/GTIN no. | 9005753100664 |
| Application | Starter battery |
| Electrical data | |
| Rated voltage | 12V |
| Rated capacity | 70 Ah (K20) |
| Cold start current | 600 A (EN) |
| Dimensions and weights | |
| Box H6 | |
| Length max. | 278mm |
| Width max. | 175mm |
| Box height max. | 190mm |
| Total height max. | 190mm |
| Battery weight | Ca. 17,5 kg (+/- 5 %) |
| Electrolyte density | Approx. 1,28 kg/l |
| Electrolyte | Diluted sulphuric acid |
| Items/pallet | 64 |
| Pallet ID | Euro pallet |
| Items per layer | 16 |
| Features | |
| Base hold-down | B13 |
| Layout | 0 |
| Terminal | 1 |
| Separator | PE bag separator |
| Degassing | Battery with central degassing |
| Flame arrester | Integrated |
| Performance identification | W4 - C2 - V1 - E1 |
| Maintenance ¹⁾ | |
| Water consumption | W4 |
| Refill water | Destilliert oder entmineralisiert (DIN 43530) |
| Self-discharge | Ca. 3 % pro Monat |
| Charging current | Ca. 1/10 der Nennkapazität |
| Charging voltage ²⁾ | max. 14,8 V |

¹⁾ All the listed values relate to room temperature +25° C

²⁾ Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2024-05-12 ; Rights relating to changes and errors retained.
original